



# Neobansaengrope



There are always rope needs, however, which have extraordinary needs in terms of rope toughness, wear resistance and anti-ageing. For customers looking to extend life beyond the outside conditions, Neotechnology has developed a product to cover that need as well.

The Neobansaengrope product is a 100% double braid rope, in which each strand of the rope has been braided, then those braided strands are braided together. This dense, hard, rope structure, while taking much more effort to manufacture, delivers the ultimate in wear and hydrolysis resistance and is the true workhorse of the Neotechnology product line while offering superior strength and anti-ageing.

Neobansaengrope is designed for bale press of waste carton box and corrugated waste paper. This rope is double heat set under tension in order to adhere to today's most demanding waste paper bale press machines.

Neobansaengrope is treated with special coating to eliminate water absorption and protect against chemical degradation.

## Technical parameters

diameter	3	3.5	4	4.5	5
weight (g/m)	5	7	9	11	13
breaking strength (kg)	200	225	250	275	300
material	polyester				
construction	hollow braided, without core				
stabilisation	high thermo-stabilisation				
metres per roll	5000	5000	5000	5000	5000
spools per palette	maximum 18				
colours	standard colours - white				

e-mail : [neotechrope@naver.com](mailto:neotechrope@naver.com)

TEL: + 82(0)32 -837-5237 FAX:+ 82(0)32 -837-5238

Adress : NEO TECHNOLOGY CO., LTD. B-504, SMART VALLY,  
SONGDO MIRAERO 30, YEONSU-GU, INCHEON-CITY, KOREA, 21990