



Neocorerope



There are always rope runs, however, which have extraordinary needs in terms of rope toughness and wear resistance. For customers looking to extend life beyond the normal, perhaps to reach the next outage cycle, Neotechnology has developed a product to cover that need as well.

The Neocorerope product is a 100% double braid rope, in which each strand of the rope has been braided, then those braided strands are braided together. This dense, hard, rope structure, while taking much more effort to manufacture, delivers the ultimate in wear and hydrolysis resistance and is the true workhorse of the Neotechnology product line while offering superior threading and tail gripping capabilities.

Neocorerope is designed for high speed applications or high wear positions including size presses, coater sections or reel sections.

Neocorerope is treated with special coating and double heating process to eliminate water absorption and protect against chemical degradation.

Technical parameters

diameter	9	10	11	12	13	15
weight (g/m)	40	52	64	76	88	101
breaking strength (kg)	1700	2200	2700	3200	3700	4250
material	Nylon(polyamide)					
construction	hollow braided, with core					
core construction	3 strand twisted core					
stabilisation	high thermo-stabilisation					
metres per roll	500	500	500	500	500	400
spools per palette	maximum 18					
colours	standard colours - yellow, red, blue and white					

e-mail : neotechrope@naver.com

TEL: + 82(0)32 -837-5237 FAX:+ 82(0)32 -837-5238

Adress : NEO TECHNOLOGY CO., LTD. B-504, SMART VALLY,
SONGDO MIRAERO 30, YEONSU-GU, INCHEON-CITY, KOREA, 21990